


# HLV Series Packing List

Heaters & Accessories

Effective 09-01-16

mm-dd-yy

All orders are subject to acceptance by Brant Radiant Heaters, Paris, Ontario at prices in effect at date of shipment. All prices are F.O.B. Paris, Ontario. All Provinces, Federal, or Municipal taxes in effect at the time of shipment or imposed at any future time on our products shall be the responsibility of the customer. We reserve the right to change specifications on our products without prior notice to the customer.



## Gas-Fired, Low Intensity, Engineered Infrared Heating Vacuum System

15% restocking charge on returned items, within 30 days from day of sale.

34 Scott Ave., Paris, Ontario N3L 3R1  
Phone: 519-442-7823 • Fax: 519-442-7321  
www.brantradiant.com • sales@brantradiant.com

### TABLE OF CONTENTS

Burners & Tube Packages .....	Page 2	Misc. Accessories .....	Page 3
Pumps & Accessories .....	Page 3	Stainless Steel Tube & Accessories .....	Page 4

Replacement parts information is available online at [www.reverberray.com/parts](http://www.reverberray.com/parts) and in the product manual.

HLV Series Marketing, Design and Installation DVD (MK-HLV) is available upon request.  
One DVD is included with each HLV Series order.

The following key symbols (found within) designate the following:

SYMBOL	DESCRIPTION
<u>Underlined Item</u>	New item or price, from prior accessory guide, or heater price sheet.
Part No. in <b>BOLD</b>	An item that has further technical information available, ex.: spec sheet, instructions, etc.

**Note:** Add-ons must be ordered as a separate line item and tagged to the appropriate heater.

**BULK PACK ORDERS** Please TAG: Job xxxxx on purchase order to help us be made aware that an order can be bulk packed to destination. 10' skid, charge \$35.00 available on request.

## BURNER PACKAGES [THLV]

Qty.	Model No.	BTU/H High Fire	BTU/H Low fire	Gas Type (circle one)	Quantity
	HLV-40	40,000	40,000	Natural or Propane	
	HLV-50	50,000	50,000	Natural or Propane	
	HLV-60	60,000	50,000	Natural or Propane	
	HLV-75	75,000	60,000	Natural or Propane	
	HLV-80	80,000	64,000	Natural or Propane	
	HLV-90	90,000	72,000	Natural or Propane	
	HLV-100	100,000	80,000	Natural or Propane	
	HLV-110	110,000	88,000	Natural or Propane	
	HLV-120	120,000	96,000	Natural or Propane	
	HLV-125	125,000	100,000	Natural or Propane	
	HLV-140	140,000	112,000	Natural or Propane	
	HLV-150	150,000	120,000	Natural or Propane	
	HLV-170	170,000	136,000	Natural or Propane	
	HLV-175	175,000	140,000	Natural or Propane	
	HLV-180	180,000	144,000	Natural or Propane	
	HLV-200	200,000	160,000	Natural or Propane	

Shipping Weight = 30 lbs.

**Included:** 1) TP-21B\*, 1) TP-19B, 1) TP-105 with 4 clips, and 1) 30 in. Type1 Rubber Gas Hose.

### Unitary Vacuum Heaters

#### IMPORTANT

Each HLV burner must be ordered with one titanium combustion chamber (TR-C).

Titanium tube must be placed first tube after burner, regardless of burner BTU.

\*Models HLV 170, 175, 180 and 200 receive TP-220 Stainless Steel Clamp.

### TUBE AND REFLECTOR PACKAGES

#### BLACK COATED TITANIUM COMBUSTION CHAMBER AND REFLECTOR PACKAGES

Qty.	Model No.	Description	Quantity
	TR-C	1) 10' x 4" Titan. tube, 1) TP-220 S.S clamp, 2) TP19B hanger, 1) TP-82 RCS	
	TR-C2	2) 10' x 4" Titan. tubes, 2) TP-220 S.S clamps, 4) TP19B hangers, 2) TP-82 RCS	
	TR-C3	3) 10' x 4" Titan. tubes, 3) TP-220 S.S clamps, 6) TP19B hangers, 3) TP-82 RCS	

#### BLACK COATED ALUMINIZED TUBE AND REFLECTOR PACKAGES

Qty.	Model No.	Description	Quantity
	10EA	1) 10' x 4" Alum. tube, 1) TP-21B clamp, 1) TP-19B hanger, 1) TP-82 RCS	
	20EA	2) 10' x 4" Alum. tubes, 2) TP-21B clamps, 2) TP-19B hangers, 2) TP-82 RCS	
	30EA	3) 10' x 4" Alum. tubes, 3) TP-21B clamps, 3) TP-19B hangers, 3) TP-82 RCS	
	TR60	1) 5' radiant tube, 1) 5' reflector, 1) TP-21B clamp, 1) TP-19B hanger	

#### UNCOATED HOT-ROLLED STEEL TUBE AND REFLECTOR PACKAGES\*

Qty.	Model No.	Description	Quantity
	10HRE	1) 10' x 4" HRT tube, 1) TP-21B clamp, 1) TP-19B hanger	
	20HRE	2) 10' x 4" HRT tubes, 2) TP-21B clamps, 2) TP-19B hangers	
	30HRE	3) 10' x 4" HRT tubes, 3) TP-21B clamps, 3) TP-19B hangers	
	HRE-60	1) 5' HRT tube, 1) 5' reflector, 1) TP-21B clamp, 1) TP-19B hanger	

\* 150-200 MBH burners with hot-rolled steel tube package require an aluminized secondary combustion chamber (10EA) to be installed immediately downstream the Titanium stabilized (TR-C) combustion chamber.

**NOTE:** All clamps, hangers and other kit items are shipped with the tubes and reflectors in 10 ft. box.

## VACUUM EXHAUSTER PACKAGES [ACVS]

Qty.	Model No.	System BTU/H	HP	VA	Inlet Adapter	Output Adapter	Quantity
	NC-7* (with panel assembly)	50-150	1/15	2.2	N/A	N/A	
	HLV-PB8 (with panel assembly)	50-275	1/2	7.6	4" (V-55A)	4" (V-55A)	
	HLV-PB9 (with panel assembly)	280-545	3/4	9.6	5" (V-56A)	4" (V-55A)	
	HLV-PB10 (with panel assembly)	550-750	1	11.4	6" (V-57A)	5" (V-56A)	

\*NC-7 is for non-condensing systems only. V-D is provided with NC-7 Pump, V-D-SS is provided with PB Series pumps.













Included with each NC-7 Pump: 1) V-D Damper, 1) Silicone, 1) TP-105 Endcap, 4) TP-106 Clips, 1) HLV IOM, 1) TP-21B 4" Clamp and 3) TP-65I Baffles.

Included with each PB Series Pump: 1) V-D-SS Stainless Damper, 1) Silicone, 1) TP-105 Endcap, 4) TP-106 Clips, 1) TP-220 SS 4" Clamp, 3) TP-65I Baffles, 2) Adapters, 2) 16" Isolation Boots, 4) Hose Clamps and 1) HLV IOM.



Note: Vacuum pumps come with a pre-assembled exhauster panel which includes a post-purge timer, fuse protection and hook-up for 24V controls. All pumps have internal overload protection. Pumps are prewired for 120V pump input (220V Optional - PB Only), 24V control.


V-1SAO = Single Stage Add-On:

## HLV SERIES ACCESSORIES

PART NO.	DESCRIPTION	Quantity	PART NO.	DESCRIPTION	Quantity
 V-D	16 in. damper used to equalize the pressure on each leg of vacuum system. 16 gauge aluminized steel, 4 in. diameter with 1) tube clamp. A V-D must be used on each run from the pump (except the longest) that has a 5' ft. (or greater) length differential from any other branch in the system.		 V-T	Tee fitting used to join two branches of a vacuum system. 16 gauge aluminized steel, 4 in. diameter tee with high temperature black coating. Includes: 1) tube clamp, 1) TP-19B, 3) end caps and 12) clips. Dimensions: 21 in. across top (with neither end swaged) by 13 in. <b>NOTE:</b> the 13 in. middle leg is swaged.	
REF-18	18 in. aluminum reflector. Includes 1) RCS, 1) end cap and 4) clips. Used to cover damper.		 V-RTE	.025 highly polished aluminum reflector used to cover a V-T or V-TI. Reflector assembly includes: left, right and center sections, 2) brackets and 15) screws.	
V-DKIT	V-D (damper) and REF-18 (reflector) package.		V-TER	V-T package with V-RTE reflector package. See illustration on page 4 for proper application.	
 E6	Elbow - 6 in. radius, 90° bend, 4 in. diameter 16 gauge aluminized steel with black coating, 1) tube clamp, 1) hanger, and 2) reflector end caps with 8) clips. Consult IOM for minimum distance from burner.		 V-TI	In-line tee fitting used to join two branches of a vacuum system. 16 gauge aluminized steel, 4 in. diameter tee, with high temperature black coating. Includes: 1) tube clamp, 1) TP-19B, 3) end caps and 12) clips. Dimensions: 21 in. across top (with one end swaged) by 13 in. <b>NOTE:</b> the 13 in. middle leg is not swaged.	
 RE	Reflector Elbow - 90° bend, with polished, one side bright, aluminum reflector elbow. Designed to fit atop one elbow (not included). Sq. dimension 27 in. x 27 in.		 V-RTE	.025 highly polished aluminum reflector used to cover a V-T or V-TI. Reflector assembly includes: left, right and center sections, 2) brackets and 15) screws.	
REP	E6 Elbow package with standard RE reflector package.		V-TERI	V-TI and V-RTE packages. See illustration on page 4 for proper application.	
 TF1B	180° fitting, used to make a U-shaped heater configuration. 16 ga. aluminized steel, 4 in. dia. fitting with high temperature black coating. Also included: 1) tube clamp, 1) wire hanger, 2) reflector end caps, and 8) clips. Adds 14 in. to overall unit length, center to center 16 in. Consult IOM for minimum distance from burner.		 V-CR	Cross fitting used to join three branches of a vacuum system. 16 gauge aluminized steel, 4 in. diameter cross with high temperature black coating. Includes: 1) tube clamp, 1) RCS, 4) end caps, and 16) clips. Swaged on one end of the four legs. Dim: 21 in. x 21 in.	
 RU	Reflector U designed to cover a TF1B fitting. 180° bend U-reflector for attachment to standard reflectors. Polished one side bright aluminum. One TP-82 RCS included. <b>NOTE:</b> reflectors cannot be rotated on a mounting angle upon installation of this RU fitting.		 V-RCR	Reflector assembly designed to cover V-CR cross fitting. Reflector is constructed .025 highly polished aluminum. Field assembled with aluminum gussets and pop rivets provided. Included are 4) center sections, 4) angle brackets, and 24) screws.	
RUP	TF1B 'U' package with standard RU reflector accessories.		V-CRP	Vacuum Cross and Reflector package. Includes V-CR and V-RCR packages.	
 45E	Elbow - 6 in. radius, 45° bend, 4 in. diameter, 16 ga. black coated aluminized steel, 1) tube clamp, 1) hanger, and 2) reflector end caps with 8) clips. Consult IOM for minimum distance from burner.		V-TTS	Tandem Tee Set. Designed to emulate in series burners. Includes 1) V-TERI, 1) V-DKIT, 1) REP, 3) TP-21B clamps, 2) TP-19B hangers and 1) TP-82 RCS. Must attach to TR-C or a minimum 10 ft. space between burner and elbow.	

## HLV SERIES ACCESSORIES

PART NO.	DESCRIPTION	Quantity
 V-TB	Turnbuckle for sloping condensing tailpipe. One piece required for each 10 ft. tube. Designed to fit standard "S" hook.	
 V-SMK	Vacuum pump sidewall mounting kit. Designed to support PB Series vacuum pumps installed on a sidewall application.	

PART NO.	DESCRIPTION	Quantity
WVE-ALUM	Aluminum sidewall vent cap with flapper. WVE is to be used for sidewall venting applications. 4 in. diameter.	
 V-PAI	Powered air inlet used to bring in outside air for combustion. To be used on runs that exceed 20 ft. but are limited to 150 ft. 5 in. intake and a 6 in. exhaust adapter are included. 265 CFM, 115V, 50/60 HZ, auto-reset and thermal protection.	




## STAINLESS STEEL TUBE AND REFLECTOR PACKAGES [ACTP]






QTY.	MODEL NO.	DESCRIPTION	Quantity
	10STP	1) Type 304 10' x 4" S.S. tailpipe w/ alum. refl., 1) TP-220, 1) TP-19B & 1) TP-82	
	20STP	2) Type 304 10' x 4" S.S. tailpipe w/ alum. refl., 2) TP-220, 2) TP-19B & 2) TP-82	
	30STP	3) Type 304 10' x 4" S.S. tailpipe w/ alum. refl., 3) TP-220, 3) TP-19B & 3) TP-82	
	STP-60	1) Type 304 5' x 4" S.S. tailpipe w/ alum. refl., 1) TP-220 & 1) TP-19B	

**NOTE:** Observe 18 in. top clearance on all condensing tailpipe not covered by a reflector. Minimum 60 ft. downstream of burner.

**NOTE:** STP packages & stainless steel accessories are not black coated unless otherwise specified.

## STAINLESS STEEL ACCESSORIES

PART NO.	DESCRIPTION	Quantity
 V-D-SS	16 in. damper used to equalize the pressure on each leg of a vacuum system. 304 stainless steel, 4 in. diameter with 1) stainless steel tube clamp. A V-D-SS must be used on each run from the pump (except the longest) that has a 5 ft. (or greater) length differential from any other branch in the system.	
V-DSKIT	V-D-SS (SS damper) and REF-18 (Alum. reflector) package.	
 E6-SS	304 grade stainless steel elbow. 6" radius, 90° bend, 4" diameter, 16 gauge with black coating. Includes (1) stainless steel tube clamp, (1) stainless steel hanger and (2) stainless steel reflector end caps with 8 clips.	
RE-SS**	Reflector Elbow - 90° bend. 304 stainless steel.	
 TF1B-SS	180° bend, used to make a U-shaped heater configuration. 16 ga. 304 stainless steel, 4 in dia. fitting with high temperature black coating. Also included: 1) stainless steel tube clamp, 1) wire hanger, 2) reflector end caps, and 8) clips.	
RU-SS**	Reflector 'U'. 304 stainless steel. 1) TP-82 RCS included. <b>NOTE:</b> Reflectors cannot be rotated on a mounting angle upon installation of this RU fitting.	

PART NO.	DESCRIPTION	Quantity
 45E-SS	Elbow - 6 in. radius, 45° bend, 4 in. diameter, 16 ga. 304 stainless steel, 1) tube clamp, 1) hanger, and 2) reflector end caps with 8) clips.	
 V-T-SS	Tee fitting used to join two branches of a vacuum system. 304 stainless steel, 4 in. diameter tee. Includes: 1) stainless steel tube clamp, 1) TP-19B, 3) end caps and 12) clips. Dim: 21 in. across top (with neither end swaged) by 13 in. <b>NOTE:</b> The 13 in. middle leg is swaged. See illustration below.	
 V-TI-SS	In-line tee fitting used to join two branches of a vacuum system. 304 stainless steel, 4 in. dia. tee. Includes: 1) s.s. clamp, 1) TP-19B, 3) end caps and 12) clips. Dim: 21 in. across top (with one end swaged) by 13 in. <b>NOTE:</b> The 13 in. middle leg is not swaged. See illustration below.	
V-RTE-SS**	304 grade stainless steel reflector used to cover a V-T-SS or a V-TI-SS.	
 V-CR-SS	Cross fitting used to join three branches of a vacuum system. 304 stainless steel, 4 in. diameter cross. Includes: 1) stainless steel tube clamp, 1) RCS, 4) end caps and 16) clips. Swaged on one end of the four legs. Dim: 21 in. x 21 in.	
V-RCR-SS**	304 stainless steel reflector used to cover a V-CR-SS.	
 V-CT	Condensate trap and 26 gauge venting tee used for condensate disposal on condensing systems. Required on vertical venting.	

### HLV Series Limited Warranty:

1 Year - Controls & Vacuum Pump.  
3 Years - Hot Rolled & Stainless Steel Tubes.  
5 Years - Aluminized & Titanium Tubes.  
10 Years - Burner.

### Extended Warranties:

CWO - Control Warranty Option (net p/ year, per burner, max. 4 years).  
EWO - Exchanger Warranty Option ( net p/ year, per tube, max. 5 years).  
VPWO - Pump Warranty Option (net p/ year, per pump, max. 4 years).

\*\* Aluminum reflector accessories are recommended for use with stainless steel accessory fittings when system is fitted with standard aluminum reflector sections. See page 3.

## PROPER TEE FITTING APPLICATION

