

## **PRODUCT FEATURES**

- Compact, aesthetically pleasing construction.
- Easy to install with minimal assembly required.
- Proven reduced energy consumption characteristics.
- Multiple construction features including: dual spark ignition, highly emissive heat exchangers, polished reflectors, operational indicator lights and more.

- Reduced Energy Consumption
- Radiant Efficiency
- Designed and packaged for ease in transportation.
- CSA Design Certified for both indoor and outdoor use and to Agricultural and Commercial/Industrial Standards.
- No Hot Spots

## **AVS SERIES**

SINGLE-STAGE, AGRICULTURAL, INFRARED QUAD TUBE HEATERS

## **PRODUCT SPECIFICATIONS**



Input Range: 40,000 to 80,000 BTU/h



Lengths: 107"



**Gas Type:** Natural or Propane



**Burner Control Box:** Coated Enameled Steel



Radiant Tubes: Black Coated Aluminized Steel



**Certification:** CSA Design Certified



Limited Warranty: 1 (Components) - 3 (Tubes) - 5 (Burner)



Electrical: 120V, 60 Hz. Amps: 1.5 Starting, 1.1 Running

## **AVAILABLE AVS MODELS & CLEARANCES**


MODEL #	GAS <sup>1</sup>	BTU/h INPUT	LENGTH	WEIGHT	MOUNTING HEIGHTS <sup>2</sup>		ТОР	SIDE	BELOW	BACK	END
AVS-40N	Natural	40,000	107"	103 lbs	8' to 10'	:S3	10	36	40	6	12
AVS-40P	Propane	40,000	107"	103 lbs	8' to 10'	ISTIBLE	10	36	40	6	12
AVS-60N	Natural	60,000	107"	103 lbs	8' to 12'	COMBL HES)	10	36	40	6	12
AVS-60P	Propane	60,000	107"	103 lbs	8' to 12'	CES TO (INC	10	36	40	6	12
AVS-80N	Natural	80,000	107"	103 lbs	10' to 14'	EARAN	10	36	40	6	12
AVS-80P	Propane	80,000	107"	103 lbs	10' to 14'	5	10	36	40	6	12



Clearance to Combustables Diagram: End View

Clearance to Combustables Diagram: Side View

Always maintain the published clearances to combustibles. Not for residential use. Clearances published in AVS Series manual and on warning label supersede data shown on this brochure.





34 Scott Ave., Paris, Ontario N3L3R1 Canada +1.519.442.7823 | sales@brantradiant.com













