

RE-VERBER-AIR HEATER  
SUBMITTAL SHEET

## FA SERIES UNIT HEATERS

## GAS-FIRED, INDUCED DRAFT, HOT AIR UNIT HEATERS &amp; ACCESSORIES

PROJECT ID: _____	ADDRESS: _____
PROJECT NAME: _____	_____
DATE: _____	CITY: _____ PROV. _____ PC: _____
Submitted By: _____	Address: _____
Company: _____	_____
Phone: _____	City: _____
Email: _____	Province: _____ Postal Code: _____
.....	
Engineer: _____	Contractor: _____
Phone/Email: _____	Phone/Email: _____
Address: _____	Address: _____
City: _____	City: _____
Province: _____ Postal Code: _____	Province: _____ Postal Code: _____

QTY.	MODEL NO.	TAG	INDICATE GAS TYPE	BTU/h		APPROX. HEAT THROW	AVERAGE AIR TEMP. RISE	VENT LENGTH <sup>1</sup>		TYP. OR RCMD. MOUNTING HEIGHTS <sup>1</sup>	SHIP WEIGHT
				INPUT	OUTPUT			MIN.	MAX.		
	FA-100		Nat. or Prop.	100,000	80,000	43 ft.	50°F	3 ft.	40 ft.	12 to 14 ft.	143 lbs.
	FA-125		Nat. or Prop.	125,000	100,000	47 ft.	50°F	3 ft.	40 ft.	14 to 16 ft.	143 lbs.
	FA-150		Nat. or Prop.	150,000	120,000	50 ft.	50°F	3 ft.	40 ft.	14 to 16 ft.	195 lbs.
	FA-175		Nat. or Prop.	175,000	140,000	52 ft.	50°F	3 ft.	40 ft.	15 to 17 ft.	195 lbs.
	FA-200		Nat. or Prop.	200,000	160,000	55 ft.	50°F	3 ft.	40 ft.	15 to 17 ft.	195 lbs.
	FA-225		Nat. or Prop.	225,000	180,000	59 ft.	50°F	3 ft.	40 ft.	16 to 18 ft.	212 lbs.
	FA-250		Nat. or Prop.	250,000	200,000	63 ft.	50°F	3 ft.	40 ft.	16 to 18 ft.	212 lbs.
	FA-300		Nat. or Prop.	300,000	246,000	67 ft.	70°F	3 ft.	40 ft.	18 to 20 ft.	296 lbs.
	FA-400		Nat. or Prop.	400,000	328,000	71 ft.	70°F	3 ft.	40 ft.	20 to 22 ft.	351 lbs.

<sup>1</sup> Deduct 5 ft. (on 4 in. vent) or 7 ft. (on 6 in. vent) for each elbow added to venting.



34 Scott Ave, Paris Ontario N3L3R1 Canada  
+1-509-442-7823 | sales@brantradiant.com

LSUH-08/23 (BRH)

## FA SERIES FEATURED SPECIFICATIONS

### APPROVALS

- ETL Listed
- Commercial/Industrial Approval
- Indoor Use Only

### VOLTAGE

- 120 VAC/60 Hz (primary)
- 24 VAC (thermostatic)
- Single phase

### MANIFOLD PRESSURE (Inches W.C.)

- Natural Gas: 3.5
- Propane: 10.0

### INLET PRESSURE (Inches W.C.)

- Natural Gas: 5.0 to 14.0
- Propane: 11.0 to 14.0

### GAS CONNECTION

- FA-100–200: ½" NPT
- FA-225–400: ¾" NPT
- Field connect to valve

### VENT & INLET CONNECTION

- Category I or III venting
- Rear, horizontal discharge/inlet

### MOUNTING

- Non-reversible horizontal mounting
- Mounting with ⅜"–16 threaded inserts (qty. 4)

### OTHER

- Finger-proof fan guards standard
- External indicator lights
- External thermostatic connection
- Approved for 0–2,000 ft. elevations without modifications
- Supplied standard as separated combustion

### LIMITED WARRANTY

- 1 year–Components
- 5 years–Heat exchangers
- 10 years–Burners

MODEL	FLA AMPS	MOTOR TYPE	MOTOR HP	FAN DIAMETER	AXIAL FAN ROTATION	GAS CONNECTION	INLET & VENT CONNECTION
FA-100	5.2	PSC	1/8	18 in.	CCW	1/2" NPT	4" O.D.
FA-125	5.0	PSC	1/6	18 in.	CCW	1/2" NPT	4" O.D.
FA-150	10.7	PSC	1/3	22 in.	CCW	1/2" NPT	6" O.D.
FA-175	10.7	PSC	1/3	22 in.	CCW	1/2" NPT	6" O.D.
FA-200	10.7	PSC	1/3	22 in.	CCW	1/2" NPT	6" O.D.
FA-225	10.7	PSC	1/3	22 in.	CCW	3/4" NPT	6" O.D.
FA-250	10.7	PSC	1/3	22 in.	CCW	3/4" NPT	6" O.D.
FA-300	11.9	PSC	3/4	26 in.	CCW	3/4" NPT	6" O.D.
FA-400	14.3	PSC	1	30 in.	CCW	3/4" NPT	6" O.D.

## FIELD CONVERSION REFERENCE CHART

SUPPLIED AS	CONVERSION TO	AVAILABILITY	PART REFERENCE <sup>2</sup>
Separated Combustion	Power Vented, Room Air	Standard	See IOPM
Natural Gas	Propane Gas	Optional	HKP
0–2,000 MSL	2,001–4,500 MSL	Optional	HKN or HKP
0–2,000 MSL	4,501–7,000 MSL	Optional	HKN or HKP
0–2,000 MSL	7,001–9,500 MSL	Optional	HKN or HKP

<sup>2</sup>Consult heater Installation, Operation, Parts, and Maintenance Manual for conversion kit reference and instructions.

## OPTIONAL ACCESSORIES

- ☐ **CVK-4** 4" Concentric Vent Kit for use when venting and combustion air is desired through a single wall or roof penetration. For use with FA-100 and FA-125 models. No vent pipe or B-vent material is included.
- ☐ **CVK-6** 6" Concentric Vent Kit for use when venting and combustion air is desired through a single wall or roof penetration. For use with FA-150 through FA-400 models. No vent pipe or B-vent is included.

☐ \_\_\_\_\_

☐ \_\_\_\_\_

☐ \_\_\_\_\_



34 Scott Ave, Paris Ontario N3L3R1 Canada  
+1-509-442-7823 | sales@brantradiant.com